












		Model	EW 450E	
		Code Production	918825	
		Interface:		
				
				
	Overall Dimension (Width-Depth-Height) *open	mm	525x555(895*) x715 (865 w/legs)	
	Packaging Dimension (W x D x H)	mm	640x580x870	
	Gross weight	Kg	49	
	Net weight	Kg	43	
	Volume	mc	0,37	
	Rack size	mm	450x450	
	Distance between rails	mm	450x450	
	Rack's drives/frame construction		flat special welded	
	Max door /hood opening	mm	300	
	Max glasses Height	mm	280	
	General construction		single skin	
	Door/hood Construction		double skin	
	Tank construction		welded	
	Tank volume	liter	14	
	Tank heating element	W	630	
	Tank surface strainers		Yes - composite	
	Wash pump type		double flow	
	Wash pump power	W	200	
	Wash temperature	°C	60	
	Boiler type		without pressure	
	Boiler volume	liter	2,6	
	Back-flow system		break tank	
	Boiler heating element	W	2.730	
	Rinse booster pump		YES	
	Rinse booster pump power	W	200	
	Rinse temperature	°C	65	
	Rinse water consumption	Liter /rack	2	
	Optimal external water pressure	bar	2 - 4	
	Optimalexternal water temperature	°C	50 – 65	
	Drain system		partial drain	
	Drain pump		standard built in	
	Rinse aid dispenser	peristaltic	YES	
	Detergent dispenser	peristaltic	YES	
	Wash cycle	sec	60 -120 -150	
	Self cleaning – drain		YES	
	Electric Power	W	3.600	
	Electric Connection	V - ph - Hz	240V 1N 50Hz	
	Fuse	A	15	
	Plates racks	n° 1	YES	
	Flat Rack	n° 1	YES	
	Cutterly Rack	n° 1	YES	
	Special legs (h15cm)	n°4	461020	
	Electric cable “Australian plug”	n°1	YES	
	Drain hose	n°1	YES	
	Fill hose “WaterMark”	n°1	YES	

